

Ø interior Inside Ø	Ø exterior Outside Ø	Peso Weight	Presión Pressure	Vacío Vacuum	Long. Lenght	Presentación Presentation	Código Code
Tolerancia: ISO 1308		+/- 5%			Min s/ISO 1307		
mm	mm	gr/m	bar	mH <sub>2</sub> O	m		
38	45	220	1,5	4	30	Rollo / Coil	695038
38	45	220	1,5	4	8	Caja / Box (*)	695008
38	45	220	1,5	4	10	Caja / Box (*)	695010
38	45	220	1,5	4	12	Caja / Box (*)	695012
38	45	220	1,5	4	15	Caja / Box (*)	695015


**Estructura / Structure:**

Tubo flexible corrugado en PEBD + EVA  
Corrugated flexible hose manufactured with LDPE + EVA

**Color / Colour:**

Azul / Blue.

**Temperatura de uso / Temp. range:**

-25 °C +65 °C

(\*) En las cajas, cada rollo lleva 2 manguitos (de rosca a izquierdas), incorporados a la manguera.

In the boxes, each coil carries 2 raccords (spiral left), incorporated to the hose.


**Aplicaciones / Applications:**

Limpeza autoflotante de piscinas.  
Swimming pool (floating) cleaning

**Características / Features:**

Alta flexibilidad y resistencia a la fatiga mecánica. Elevadísima flotabilidad.  
Fabricada de una sola pieza (sin colas ni plastificantes)

High flexibility and resistance to mechanical fatigue. Very high floating.  
Manufactured in one piece (without glue. Not treated with plastic)

Los valores de vacío y presión corresponden a temperaturas de trabajo de 20 °C. Flexiplas se reserva el derecho de modificar las especificaciones sin previo aviso.  
The detailed values of resistance to vacuum and pressure correspond to working temperatures between 20°C. Specifications are subject to change without notice.